TR-350 Truck Refrigeration Units Introduction

ZHENGZHOU GUCHEN INDUSTRY CO., LTD. Website: www.guchen.com





 ADD: 1908, TIANYI MANSION, 129 HUANGHE RD, (450008) ZHENGZHOU, CHINA

 TEL: +86 371 69152893
 FAX: +86 371 69152894
 <u>http://www.guchen.com/</u>

TR-350 truck refrigeration units, directly driven by engine can meet transporting cooling requirement of chiller or frozen. They are suitable for 15m ³-25m ³refrigerated truck bodies.

The condenser is designed to streamlines, which make it has a fashionable appearance. Besides that, with its extra-slim evaporator, the space in the inside of truck box is saved much which increases the loading capacity.

With its big cooling capacity, ensure the cargo keep safe and fresh. Even in the high temperatures or frequently load and unload frequently, the big cooling capacity can also keep products safe and fresh.



Main Features:

- 1. High air volume, good efficiency, keeps the quality of the goods in the box.
- 2. Easy installations, convenient maintenance, and saving operating costs.
- 3. Durable body construction to allow for extended life.
- 4. Corrosion resistant fiberglass outermost shell
- 5. Temperature range adjustable from -30 $^{\circ}$ C to + 30 $^{\circ}$ C



2. DIMENSIONS: 470×460×330mm (36kg)



ZHENGZHOU GUCHEN INDUSTRY CO., LTD.

 ADD: 1908, TIANYI MANSION, 129 HUANGHE RD, (450008) ZHENGZHOU, CHINA

 TEL: +86 371 69152893
 FAX: +86 371 69152894
 <u>http://www.guchen.com/</u>

Model		TR350	
Temperature Range(In Container)		-20℃ ~+25℃	
Cooling Capacity	0℃/+32 ℉	3815W / 4437Kcal/h / 13020BTU	
	-18°C/0°F	2260 / 2628Kcal/h / 7710 BTU	
Compressor	Model	QP16	
	Displacement	163cc/r	
Condenser	Coil	Aluminum micro-channel parallel flow	
		coils	
	Fan	Spal	
	Dimensions	1010×553×230 mm	
	Weight	21 kg	
Evaporator	Coil	Aluminum foil with internal ridge copper	
		tube	
	Fan	Spal	
	Dimensions	1105×649×230 mm	
	Weight	17 kg	
Voltage		DC12V / DC24V	
Refrigerant		R404a/1.5kg	
Defrosting		Hot gas defrosting(Auto./Manual)	
Application		L≪4.5m /15~25m³	



ZHENGZHOU GUCHEN INDUSTRY CO., LTD.

 ADD: 1908, TIANYI MANSION, 129 HUANGHE RD, (450008) ZHENGZHOU, CHINA

 TEL: +86 371 69152893
 FAX: +86 371 69152894
 http://www.guchen.com/

Key Parts List:					
Mark	Name	Model	Features	Quantity	
1	Compressor	QP16	High efficiency, long service life	1 Set	
2	Condenser Fan	SPAL (Italy)	<u>Axial flow</u> ,High efficiency, long service life	1 Set	
3	Evaporator Fan	SPAL (Italy)	Brushless Fan ,large air flow, lower noise	2 Sets	
4	Expansion Valve	Danfoss (Denmark)	Good interchangeability performance, with MOP	1 Set	
5	Reservoir	GUCHEN	Reasonable design, plastic powder coating surface	1 Set	
6	Filter Drier	Danfoss (Denmark)	Strong drying and filtering capability	1 Set	
7	Sight glass	Danfoss(Denmark)	Fully Display	1 Set	
8	Crankcase Pressure Regulator	Danfoss (Denmark)	Regulate the crankcase pressure, effectively protect the compressor	1 Set	
9	Oil separator	GUCHEN	Reliable performance, good protection to the compressor	1 Set	
10	Solenoid Valve	Castel (Italy)	Liquid injection valve, Defrosting valve	2 Sets	
11	Exhaust senor	BPT(Joint Venture)	Control the displacement, protect the compressor	1 Set	
12	Condenser Coil	TR350-L	Brazed aluminium microchannel condenser coil	1 Set	
13	Evaporator Coil	TR-350Z	Inner grooved cooper Tube & hydrophilic fin	1 Set	
14	Control Panel	GUCHEN	Controlled by the integrated circuit, easy for handle	1 Set	
15	Shell	GUCHEN	FRP, beautiful, strong, corrosion and aging resistance	1 Set	
16	Refrigerant Pipe	Codan (Joint Venture)	Aging resistance and easy for installation	1 Set	